




PROJECT NAME	
CATALOG NUMBER	
NOTES	
FIXTURE SCHEDULE	

LED TROFFERS



FEATURES & BENEFITS

- 100-277VAC, 0-10V dimmable
- 5 Years warranty
- CRI: 80+
- Daisy-chainable
- Diffuser with anti-yellowing technology
- Ideal replacement for traditional troffer with over 80% energy saving

- Light weight
- No flicker. No glare. Even light distribution without dark spots
- No sharp edges • PF: 0.9+, THD ≤ 15%
- Very high efficacy: up to 139 lm/W
- Quick and easy installation
- UL, cUL, and DLC certifications

APPLICATIONS

- Offices
- Classrooms
- Retail
- Hotels
- Restaurants
- Healthcare Facilities

LED TROFFERS

ORDERING INFORMATION

QUICK SHIP	Model Number	Size	Dimmable	Power (W)	Lumen Output	Efficiency (lm/W)	Input Voltage	CCT (K)	CRI	DLC Certification	Weight
	TL22QW28AC30DW01-S	2 x 2	Yes	28	3200	114	100V - 277V	3000	80	DLC Standard	5.1 lbs
X	TL22QW28AC40DW01-S	2 x 2	Yes	28	3300	118	100V - 277V	4000	80	DLC Standard	5.1 lbs
	TL22QW28AC50DW01-S	2 x 2	Yes	28	3400	121	100V - 277V	5000	80	DLC Standard	5.1 lbs
	TL22QW35AC30DW01-S	2 x 2	Yes	35	3900	111	100V - 277V	3000	80	DLC Standard	5.1 lbs
X	TL22QW35AC40DW01-S	2 x 2	Yes	35	4000	114	100V - 277V	4000	80	DLC Standard	5.1 lbs
	TL22QW35AC50DW01-S	2 x 2	Yes	35	4200	120	100V - 277V	5000	80	DLC Standard	5.1 lbs

	TL24QW36AC30DW01-S	2 x 4	Yes	36	4300	119	100V - 277V	3000	80	DLC Standard	8.6 lbs
X	TL24QW36AC40DW01-S	2 x 4	Yes	36	4500	125	100V - 277V	4000	80	DLC Standard	8.6 lbs
	TL24QW36AC50DW01-S	2 x 4	Yes	36	4600	128	100V - 277V	5000	80	DLC Standard	8.6 lbs
	TL24QW45AC30DW01-S	2 x 4	Yes	45	5300	118	100V - 277V	3000	80	DLC Standard	8.6 lbs
X	TL24QW45AC40DW01-S	2 x 4	Yes	45	5400	120	100V - 277V	4000	80	DLC Standard	8.6 lbs
	TL24QW45AC50DW01-S	2 x 4	Yes	45	5600	124	100V - 277V	5000	80	DLC Standard	8.6 lbs
	TL24QW50AC30DW01-S	2 x 4	Yes	50	5700	114	100V - 277V	3000	80	DLC Standard	8.6 lbs
	TL24QW50AC40DW01-S	2 x 4	Yes	50	5900	118	100V - 277V	4000	80	DLC Standard	8.6 lbs
	TL24QW50AC50DW01-S	2 x 4	Yes	50	6000	120	100V - 277V	5000	80	DLC Premium	8.6 lbs
	TL24QW60AC30DW01-S	2 x 4	Yes	60	6600	110	100V - 277V	3000	80	DLC Standard	8.6 lbs
X	TL24QW60AC40DW01-S	2 x 4	Yes	60	6800	113	100V - 277V	4000	80	DLC Standard	8.6 lbs
	TL24QW60AC50DW01-S	2 x 4	Yes	60	7000	117	100V - 277V	5000	80	DLC Premium	8.6 lbs

Note 1: Quick Ship items identified with X and is product supported with Inventory in the US. Other product is order on request.

Note 2: Material supplied in Standard cartons. Carton contains quantity 2.

TECHNICAL SPECIFICATION

- Input voltage: 100 - 277 VAC, 50 - 60 Hz
- THD: $\leq 15\%$
- PF: >0.9 with no flicker
- Color Temperatures: 3000K, 4000K, 5000K

- Color Rendering Index: CRI >80
- Operating Temperature: -4F to +122F
- Rated Life: 50,000 Hours

